

KEY LEGEND

KEY	TEXT
A1	(E) ACCESSIBLE GIRL'S RESTROOM A# 115568
A2	(E) ACCESSIBLE BOY'S RESTROOM A# 115568
A3	(E) ACCESSIBLE RESTROOM A# 115568
A4	(E) ACCESSIBLE STAFF UNSEX RESTROOM A# 115568
A5	(E) ACCESSIBLE H-LO DRINKING FOUNTAIN A#115568
A7	(E) ACCESSIBLE STEEL PEDESTRIAN GATE - A# 115568
A9	(E) ACCESSIBLE ADMINISTRATION LOBBY VISITOR CHECK-IN - A#106196
A10	(E) ACCESSIBLE WHEELCHAIR LIFT - A#106196
A11	(E) ACCESSIBLE RAMP AND STAIRS - A#106196
A12	(E) ACCESSIBLE H-LO DRINKING FOUNTAIN - A#106196
A13	(E) ACCESSIBLE GIRL'S RESTROOM - A#106196
A14	(E) ACCESSIBLE BOY'S RESTROOM - A#106196
A15	(E) ACCESSIBLE UNSEX RESTROOM - A#106196
A16	(E) ACCESSIBLE STAFF UNSEX RESTROOM - A#106196
A17	(E) ACCESSIBLE STAFF UNSEX RESTROOM - A#101443
A18	(E) ISA SIGN ON DOOR
A19	(E) 5% SLOPED WALK
A20	(E) NON-ACCESSIBLE WOMEN'S RESTROOM
A21	(E) NON-ACCESSIBLE MEN'S RESTROOM
A22	(E) NON-ACCESSIBLE STAFF UNSEX RESTROOM
A24	(E) ACCESSIBLE ENTRY DOORS - A#106196
A25	(E) ACCESSIBLE DRINKING FOUNTAIN-A#03-117210
S1	(E) 6'-0" H STL FENCING, PAIR OF 6'-0" W GATES AND SINGLE 3'-0" W PEDESTRIAN GATE W/ WELDED WIRE MESH PANELS - A#115568
S2	(E) 6'-0" H CHAIN LINK FENCE W/ 4'-0" W PEDESTRIAN GATE (E)
S3	(E) PLANTING AREA W/ 1" CUT BARK WOOD MULCH (OAK, PINE, OR REDWOOD) A#115568
S5	(E) CONCRETE PAVING
S6	(E) CONCRETE PAVING
S7	(E) ASPHALT PAVING
S9	(E) RETAINING WALL & CONCRETE BENCH
S11	(E) 6'-0" H CHAIN LINK FENCE W/ 3'-0" W PEDESTRIAN GATE A#115568
S14	(E) STEEL PLANTER HEADER
S15	(E) LUNCH SHELTER A#13410
S16	(E) CURB RAMP
S17	(E) CURB CUT
S18	(E) PLANTING AREA
S20	(E) MARQUEE
S21	(E) FLAGPOLE
S22	(E) RUBBER SURFACING
S23	(E) TRASH ENCLOSURE
S24	(E) ELECTRICAL EQUIPMENT
S25	(E) PV INVERTER ON CONCRETE PAD
S31	(E) CHAIN LINK FENCE
S32	(E) CONCRETE STAIRS
S33	(E) CONCRETE RAMP A#106196
S34	(E) SHADE STRUCTURE
S36	(E) 20'-0" SWING GATE PROTECT IN PLACE
S37	(E) 18'-0" WIDE SLIDING GATE
S38	(E) STEEL ENTRY GATEWAY
S42	STREET CENTERLINE
S43	PROPERTY LINE - TYP.
S44	IMAGINARY PROPERTY LINE
S51	(E) 3'-0" MAN GATE
S52	(E) FIRE DEPARTMENT MAN GATE
S53	CONCRETE PAVING
S54	(E) SITE STAIR
S72	(E) WOOD HANDBALL WALL
S73	(E) BENCH
S76	(E) ELECTRIC BOX - A#115568
S77	(E) TRANSFORMER - A#115568
S78	LIMIT OF WORK
S80	(E) BIKE RACKS
S82	STRIPPING
S89	(E) RETAINING WALL
S90	END OF (E) RETAINING WALL
S94	(E) 3'-0" CLF PEDESTRIAN GATE
S95	BASKET BALL GOAL SEE 1/G002
S96	(E) FIRE LANE PER SEE REFERENCE
S97	(E) STORAGE CONTAINER, TYP- PLACED BY DISTRICT
S98	ACCESSIBLE DIRECTIONAL SIGNAGE, SEE 3/G002
S98	ALS SIGNAGE, ALS SYSTEM PROVIDED 03-115568 DEVICE AVAILABLE IN ADMIN OFFICE

1 CODE ANALYSIS & ACCESSIBILITY SITE PLAN

LEGEND

(Tree symbol)	TREE	(Dotted pattern)	DECOMPOSED GRANITE	(Hatched pattern)	(E) BRICK PAVING	(Hatched pattern)	(E) ACCESSIBLE RESTROOMS	(Hatched pattern)	PERMEABLE PAVERS
(Dotted pattern)	(E) TREE	(Dotted pattern)	(E) ASPHALT PAVING	(Hatched pattern)	(E) RUBBERIZED TILE SURFACING	(Hatched pattern)	(E) ACCESSIBLE RESTROOMS	(Hatched pattern)	
(Dashed line)	(E) 6'-0" H CHAIN LINK FENCE	(Dotted pattern)	(E) CONCRETE PAVING	(Dotted pattern)	GRASS	(Hatched pattern)	(E) NON-ACCESSIBLE RESTROOMS	(Hatched pattern)	
(Dashed line)	(E) 6'-0" H ORNAMENTAL FENCE	(Dotted pattern)	LANDSCAPE AREA 2	(Dotted pattern)	LANDSCAPE AREA 1	(Hatched pattern)	ELEVATOR OR WHEELCHAIR LIFT	(Hatched pattern)	
(Circle)	(E) LIGHT POLE								
(Square)	30 X 48 WHEELCHAIR ACCESSIBLE SPACE								

PROJECT STATUS

DSA #	CLOSED WITH CERTIFICATION
A#7589	CERTIFIED 04/05/1991
A#1340	CERTIFIED 03/05/1998
A#101287	LETTER TYPE 1 04/16/2001
	PORTABLES
A#10143	LETTER TYPE 2 07/25/2003
A#10435	LETTER TYPE 1 06/21/2001
A#106196	LETTER TYPE 1 03/21/2005
A#115568	LETTER TYPE 1 09/21/2016
A#117210	UNDER CONSTRUCTION

FLOOD ZONE

BASED ON FLOOD INSURANCE RATE MAP DATED SEPT 26, 2008
 FLOOD ZONE X
 BASE FLOOD ELEVATION: N/A

GENERAL NOTES:

- Site walkways shall provide a barrier free path of travel for a person in a wheelchair. The path of travel shall be a hard, durable and slip resistant route a minimum of 48 inches in width (11B-4035.1 Exception 3) and with a maximum gradient slope of 5% and maximum cross-slope of 2% (11B-4033) abrupt changes in level shall not exceed a beveled slope of 1:2 with a 1/2" in vertical height and 1/4" maximum in vertical differential levels. Concrete finish shall be medium salted.
- Path of travel (P.O.T.) as indicated, is a common barrier free egress/access route without any abrupt vertical changes exceeding 1/2" beveled at 1:2 maximum slope, except that level changes do not exceed 1/4" vertical and is at least 48" wide. The path surface is slip resistant, stable, firm, and smooth. Passing spaces (11B-4035.3) at least 60" x 60" are located not more than 200' apart. Parts of P.O.T. with continuous gradients have 60" level areas (11B-403.7) not more than 400' apart. The cross-slope does not exceed 2% and slope in the direction of travel and is less than 5% unless otherwise indicated. P.O.T.'s shall be maintained free of overhanging obstructions to 80" minimum (11B-307.4) and protruding objects greater than 4" projection from wall and above 27" and less than 80" (11B-307.2). Architect shall verify that there are no barriers in the P.O.T.
- Gates in Path of travel shall have emergency hardware and kick plates.
- For all site gradients see CIVIL PLANS.
- Contractor to adjust door operation pressure to be 5 lb. MAX at all doors along the path of travel.


PATH OF TRAVEL STATEMENT

The POT identified in these construction documents is compliant with the current applicable California Building Code accessibility provisions for path of travel requirements for alterations, additions and structural repairs. As part of the design of this project, the POT that were determined to be noncompliant 1) have been identified and 2) the corrective work necessary to bring them into compliance has been included within the scope of this project's work through details, drawings and specifications incorporated into these construction documents. Any noncompliant elements, components or portions of the POT that will not be corrected by this project based on valuation threshold limitations or a finding of unreasonable hardship are so indicated in these construction documents.

During construction, if POT items within the scope of the project represented as code compliant are found to be nonconforming beyond reasonable construction tolerances, they shall be brought to compliance with the CBC as a part of this project by means of a construction change document.

REVISIONS

CONSTRUCTION DOCUMENTS



FRANKLIN E.S. URBAN GREENING GRANT
 1610 LAKE STREET, GLENDALE CA 91201
 837 N SPRING STREET LOS ANGELES CA 90012-2323 P: 323.475.8075 F: 323.475.8074



NAC ARCHITECTURE
 nacarchitecture.com
 837 N SPRING STREET, 1 THIRD FLOOR
 LOS ANGELES, CA 90012
 P: 323.475.8075

NO. 161-14031
 AUTHOR
 CHECKER
 DATE 5-30-2017

CODE ANALYSIS & ACCESSIBILITY SITE PLAN

G1.01